



### Output Ratings

Generating Set Model	HPS 1250	HPS 1375E
380 – 415V , 50 HZ	1250.0 KVA 1000.0 KW	1375.0 KVA 1100.0 KW

\*Ratings at 0.8 Power Factor

**Prime Power – Model HPS 1250:** These ratings are applicable for supplying continuous electrical power (at variable load) in Lieu of Commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

**Standby Power – Model HPS 1375E:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3)

### Technical Data

Engine Model	Perkins 4012-46TWG2A
Alternator Model	Stamford PI 734B
Number Of Cylinders	12 Vee
Cubic capacity: Liters (cu.in)	45.8 (2797.5)
Bore/Stroke: mm (in)	160 (6.3) / 190 (7.5)
Compression ratio	13.1:1
Aspiration	Turbocharged, AA Charge Cooled
Frequency	50 HZ
Engine Speed	1500 RPM
Gross Engine Power: KW(hp)	1217.0 (1632)
BMEP: KPA (psi)	2124.0 (308)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)
Fuel Consumption: HPS 1250 : 1/hr (USG/hr)	257.1 (67.9)
Fuel Consumption: HPS1375E : 1/hr (USG/hr)	283.8 (75)
Heat Rejection to Exhaust System : KW (Btu/min)	1001.0 (56926)
Heat rejection to Cooling System: KW (Btu/min)	401.0 (22804)
Total Radiated Heat: KW (Btu/min)	89.0 (5061)
Exhaust Temperature: °C (°F)	422 (792)
Radiator Cooling Air Flow: m3/min (cfm)	1116.0 (39411)
Combustion Air Flow: m3/min (cfm)	109.0 (3849)
Exhaust Gas Flow: m3/min (cfm)	180.0 (6357)

### Dimensions and Weights

Length: mm(in)	Width: mm(in)	Height: mm(in)	Dry: kg(lb)	Wet: kg(lb)
4820 (189.8)	1895 (74.6)	2424 (95.4)	9059 (19972)	9255 (20404)

\*Generating set pictured may include optional accessories



## HPS 1250-1375E

**Note:** Standard reference conditions 27 °C (80 °F) Air Intel Temp, 152.4m (500ft) A.S.L 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2