



### Output Ratings

Generating Set Model	HPS250	HPS275E
380 – 415V , 50 HZ	250.0 KVA 200.0 KW	275.0 KVA 220.0 KW

**\*Ratings at 0.8 Power Factor**

**Prime Power – Model HPS 250:** These ratings are applicable for supplying continuous electrical power (at variable load) in Lieu of Commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

**Standby Power – Model HPS 275E:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3)

### Technical Data

Engine Model	Perkins 1306C-E87TAG6
Alternator Model	Stamford UCI 274K
Number Of Cylinders/Alignment	6in line
Displacement: Liters (cu.in)	8.7 (530.9)
Bore/Stroke: mm (in)	116.6 (4.6) / 135.9 (5.4)
Compression ratio	16.9:1
Induction	Turbocharged Air To Air Charge Cooled
Frequency	50 HZ
Engine Speed	1500 RPM
Gross Engine Power: KW(hp)	250.9 (336.0)
BMEP: KPA (psi)	2306.0 (334.4)
Piston Speed: m/sec (ft/sec)	6.8 (22.3)
Fuel Tank Capacity: Liters (US Gal)	350 (92.5)
Fuel Consumption: HPS 250 : 1/hr (USG/hr)	58.9 (15.6)
Fuel Consumption: HPS 275E : 1/hr (USG/hr)	63.3 (16.7)
Heat Rejection to Exhaust System : KW (Btu/min)	142.0 (8075)
Heat rejection to Water & Lube Oil: KW (Btu/min)	110.0 (6256)
Heat Radiated to Room: KW (Btu/min)	44.0 (2502)
Exhaust Temperature: ° C ( ° F)	528 (982)
Radiator Cooling Air Flow: m3/min (cfm)	424.2 (14980)
Combustion Air Flow: m3/min (cfm)	16.4 (579)
Exhaust Gas Flow: m3/min (cfm)	44.5 (1572)

### Dimensions and Weights

Length: cm	Width: cm	Height: cm	Weight: kg
290	99	170	2252

\*Generating set pictured may include optional accessories



## HPS 250-275E

**Note:** Standard reference conditions 27 ° C (80 ° F) Air Intel Temp, 152.4m (500ft) A.S.L 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2